

SP-C AL 120/80 separation corner profile

Part No.: 2002



Application area

The SP-C AL 120/80 is part of our prefabricated metal corner range for the SP separation range that we offer. SP-C AL 120/80 separation corner profiles are primarily designed to serve as corner elements for the SP AL 120/80 profiles and to form the required gravel retention trims surrounding the ArchiGreen® inspection chambers. Alignment of the SP-C AL 120/80 with the SP AL 120/80 linear gravel retention trims is only possible if the upright side of the retention trim is 80 mm.

Benefits

- ☑ provides aesthetically pleasing demarcations among the various media and aggregate present on the green roof
- ☑ quick and easy to install without the need for mortar bedding
- ☑ does not impede drainage
- ☑ can be used to create corners with any angle of inclination
- ☑ manufactured from 1.0 mm thick aluminium plates as opposed to the 0.8 mm in

Technical data

Height	120 mm
Width	80 mm
Length	1000 mm
Plate thickness	1.2 mm
Weight	0.82 kg/m
Material	Aluminium
Effective drainage area	4200 mm ² /m
Accessory	1 pcs connector/corner element
Packaging unit	10 pcs shrink-wrapped (1 bundle)

Specification suggestion

ArchiGreen® SP-C AL 120/80 is an L-shaped, prefabricated corner, folded 5 times, made from aluminium. This prefabricated corner profile provides professional and aesthetic demarcations among various aggregates on a green roof. Material thickness: 1.2 mm; size: 1000x80x120 mm (LxWxH); drainage area: ~ 4200 mm²/m; weight: 0.82 kg/m; incl.: a single connector/profile.

Dimensions

