

TG-A GS 500 height adjustable green roof gully

Part No.: 3215



Application area

The TG-A GS 500 is part of our TG-A GS height adjustable drainage gully range. TG-A GS 500 drainage gullies are designed to efficiently discharge surface water in paved area settings set for pedestrian traffic only and allow for easy inspection and quick maintenance of the outlets.



Benefits

- ☑ height is infinitely adjustable within a given range, which makes it easy to accurately install the channel flush with its surrounding
- ☑ the narrow-spaced openings of the grating prevent larger debris from entering and blocking the outlets
- ☑ allows for easy inspection and quick maintenance of the outlets
- ☑ also available in adjustable height ranges of 73-103 mm, 93-143 mm és 113-183 mm
- ☑ perforated ballast retention ring prevents grit and surrounding growing media debris from entering the outlet
- ☑ also available in stainless steel

Technical data

| | |
|----------------|--|
| Height | H1 = 73-103 mm / H2 = 93-143 mm / H3 = 113-183 mm |
| Width | 500 mm |
| Length | 500 mm |
| Weight | 11.50 kg |
| Grating | Mesh grid |
| Mesh size | 30 x 10 mm |
| Material | Galvanized steel (Available in stainless steel) |
| Load class | Pedestrian load rated class A15 |
| Packaging unit | 24 pcs/pallet |

Specification suggestion

ArchiGreen® TG-A GS 500 height-adjustable terrace grille withstands pedestrian traffic. It allows for the drainage of surface water in paved roof terraces and for the inspection and maintenance of roof outlets. Features incl.: made of galvanized steel; mesh size is 30x10 mm; load class: A15; size: 500x500xoptional height adjuster brackets that fall into any of the following height range: (H1) 73-103 mm / (H2) 93-143 mm / (H3) 113-183 mm (LxWxH); weight: 11.50 kg. Available in stainless steel as well.

Dimensions

