# TP 5 height adjustable terrace pedestal

Part No.: 4005





## Application area


TP 5 is part of our TP paving and decking supports range. They are designed to support roof terraces made of any kind of material: timber, composite wood, concrete, metal etc. where requested height varies between 230 and 315 mm. It can be placed on any kind of stable substrate and over insulation panels. Coupled with the tabs on top, it can provide permanent spacing between the slabs to enhance better drainage.

## **Benefits**

- ☑ within a preset height range, the height is infinitely adjustable
- ☑ adjacent surfaces with different heights can be levelled to a preset single height easily
- ☑ quick and easy installation without the need to fix it to the plinth
- ☑ lightweight structures with high loadbearing capacity (1000 kg/pedestal)
- ☑ long lifespan, resistant to UV, climate changes and almost all chemicals
- ☑ coupled with spacers, the placement of paving slabs can be appropriately solved on a terrace or patio

## Specification suggestion

ArchiGreen® TP 5 screw jack terrace pedestal is made of UV-resistant copolymer polypropylene (CPP) and talc and is black in colour. Specifically designed to support outdoor green roof terraces. The TP 5 comprises two elements: 1. The Top (Ø170 mm, surface area is 22,700 mm<sup>2</sup>) able to accommodate batten clips and spacers and consequently can provide permanent spacing between the slabs to facilitate drainage for terraces on building structures in accordance with German FLL Guidelines; 2. The Base (Ø197 mm, surface area is 30,500 mm<sup>2</sup>) able to accommodate a slope corrector (TP-SC: 0 to 5%); Height of pedestal: 230-315 mm. Weight: 0.892 kg/pedestal. Resistant to UV, climate changes, sea salt and almost all chemicals. Temperature range: -30 °C to +90 °C.



## Dimensions

